

व्यावसायिक परीक्षण रिपोर्ट
COMMERCIAL TEST REPORT



संख्या / No.: Imp-238/313
माह / Month: July, 2018



**GREENSYSTEM ROTARY TILLER, Model: RT 6010 (Gear Drive)
(Tractor Operated)**



सत्यमेव जयते

भारत सरकार

GOVT OF INDIA

कृषि एवं किसान कल्याण मन्त्रालय

MINISTRY OF AGRICULTURE & FARMERS WELFARE

कृषि, सहकारिता एवं किसान कल्याण विभाग

DEPARTMENT OF AGRICULTURE, COOPERATION & FARMERS WELFARE

उत्तर पूर्वी क्षेत्र कृषि यंत्र प्रशिक्षण एवं परीक्षण संस्थान

NORTH EASTERN REGION FARM MACHINERY TRAINING & TESTING INSTITUTE

विश्वनाथ चारिआलि, जिला- विश्वनाथ (असम)

BISWANATH CHARIALI: BISWANATH: ASSAM, PIN - 784 176

[AN ISO 9001:2015 CERTIFIED INSTITUTION]

Website: <http://nerfmtti.nic.in>

Ph. No. 03715-222094

Fax No: 03715-230358

E-Mail: fmti-ner@nic.in

8. EASE OF OPERATION & ADJUSTMENTS

The operator can easily adjust and control the implement from operator's seat in the field as the adjustments are within the easy reach of operator. However the operator has to get down from the tractor in order to raise/lower the depth adjusting skids. No noticeable difficulty was observed during the operation and adjustment of Rotary tiller

9. DEFECTS, BREAKDOWNS AND REPAIRS

No breakdown was occurred during 42.6 h of wet land and dry land operation.

10. SUMMARY OF OBSERVATIONS, COMMENTS AND RECOMMENDATIONS

- 10.1 The dimension of three point linkage (hitch pyramid) of the rotary tiller does not conform to IS: 4468-1997. This should be looked into for corrective action for standardization.
- 10.2 Dimensions of PIC and PIC yoke bore of implement do not conform to IS: 4931-1995 and therefore, it should be looked into for corrective action.
- 10.3 Chemical composition of rotor blades does not conform to IS: 6690-2002. The percentage of carbon and manganese content in composition of rotavator blade material was recorded as 0.300 and 1.058 % respectively. The carbon content was on lower side and manganese content was on higher side when compared with the relevant Indian Standard. Moreover, the hardness of rotor blades also does not conform to relevant Indian Standard. It is therefore, recommended that the material of rotavator blade should be improved and provided as per requirement of Indian Standard.
- 10.4 The rate of work was recorded 0.272 to 0.305 ha/h at forward speed of 3.52 to 3.65 kmph in dry land operation.
- 10.5 The depth of operation in dry land operation was recorded as 7 to 9 cm with soil moisture content of 15.2 to 20.4 % in sandy loam soil and considered on lower side. The depth of puddle was recorder as 23 to 25 cm which is considered as normal for wetland operation.
- 10.6 The hourly rate of wear of blade on mass basis in Dry land & Wet land operations was recorded as 0.14 to 0.17% and 0.03 to 0.05% respectively.
- 10.7 The hourly rate of wear of blade on dimensional basis in Dry land & Wet land operations was recorded as 0.01 to 0.38.% and as 0.01 to 0.22% respectively.
- 10.8 **Labelling plate:**
Manufacturer's name and serial no. were indicated on the labeling plate. However, it is recommended to specify labelling plate as per Indian Standard.
- 10.9 No ingress of mud and/or water was found in primary and secondary reduction boxes after 42.6 hr of field operations and the sealing provided on different subassemblies were found effective.

**10.10 Technical literature:**

An Operator cum Service Manual & Parts Catalogue was provided along with the machine during the course of testing. It is further recommended to bring out these manuals in Hindi and other vernacular languages as per IS: 8132-1999.

TESTING AUTHORITY

S. G. PAWAR AGRICULTURAL ENGINEER	
A.K. UPADHYAY SENIOR AGRICULTURAL ENGINEER	
K.K. NAGLE DIRECTOR	

Draft test report compiled by -

Sh. Rahul Prajapati & Sh. Abhishek Tiwari

11. APPLICANT'S COMMENTS

Para No.	Our reference	Applicant's Comments
11.1	10.1	We agree with the recommendations and will provide implement hitch for Rotary Tiller conforming Cat-I to Indian Standards IS: 4468-2012.
11.2	10.2	We agree with the recommendations on PIC Yoke bore and PIC of rotary tiller and will make necessary corrections to dimensions of implement to conform to IS: 4931-1995.
11.3	10.3	We agree with recommendations and rotor blades conforming to IS: 6690-1981 on chemical composition for Carbon and Manganese content and hardness at the edge portion.
11.4	10.6 & 10.7	We agree with recommendation provided to us and we would improve to control the wear of blades.
11.5	10.8	We agree with the recommendation and parameters on labelling plate with sufficient information.
10.6	10.10	We agree with the recommendation and we will provide the booklet in Hindi and other local languages conforming as per IS 8132-1999. Booklet will include tractor compatibility sheet.